

Hanging scales KERN HDB-N · CH



KERN HDB-N



KERN CH



Convenient, economical and always handy

Features

- With the TÜV certification mark, the scale meets the requirements of the standard EN 13155 (Non-fixed load lifting attachments) and EN 61010-1 (Electrical safety)
- Ideal for rapid control in goods-in and goods-out
- Essential too in the private sector to determine the weight of fish, game, fruits, bicycle parts, suitcases etc.
- **Data hold function:** For easy reading of the weighing result, the display can be “frozen” in different ways. Either automatically when the weighing value remains unchanged or manually by pressing the Hold key

Technical data

- HDB-N:**
- **Hook (stainless steel)**, can be hinged
 - **Ready for use:** Batteries included, 2 x 1.5 V AAA, operating time up to 180 h, AUTO-OFF function to preserve the battery, can be switched off
 - Further weighing units: kg, lb, N
 - Permissible ambient temperature 5 °C / 35 °C

CH:

- **Hook (stainless steel)**
- **Tape measure**, extractable, length approx. 100 cm
- **Peak load display** (peak hold), measuring frequency 5 Hz
- **Ready for use:** 9 V Block included, operating time up to 20 h. AUTO-OFF function to preserve the batteries, can be switched off
- Further weighing units: kg, lb, N
- Permissible ambient temperature 5 °C / 35 °C

STANDARD



OPTION



| Model | Weighing range [Max] kg | Readout [d] g | LCD display, digit height mm | Dimensions housing WxDxH mm | Height with hook mm | Net weight approx. kg | Option DAKKS Calibr. Certificate | |
|-------------------|-------------------------|---------------|------------------------------|-----------------------------|---------------------|-----------------------|----------------------------------|--|
| | | | | | | | DAKKS KERN | |
| KERN | | | | | | | | |
| HDB 5K5N | 5 | 5 | 12 | 70x25x105 | 195 | 0,15 | 963-127 | |
| HDB 10K10N | 10 | 10 | 12 | 70x25x105 | 195 | 0,15 | 963-128 | |
| CH 15K20 | 15 | 20 | 11 | 90x30x176.5 | 270 | 0,25 | 963-128 | |
| CH 50K50 | 50 | 50 | 11 | 90x30x176.5 | 270 | 0,25 | 963-128 | |
| CH 50K100 | 50 | 100 | 11 | 90x30x176.5 | 270 | 0,25 | 963-128 | |

KERN Pictograms

| | | |
|--|---|--|
|  Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven). |  Recipe level A: Separate memory for the weight of the tare container and the recipe ingredients (net total). |  Suspended weighing: Load support with hook on the underside of the balance. |
|  Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required. |  Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display. |  Battery operation: Ready for battery operation. The battery type is specified for each device. |
|  Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc. |  Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display. Additional convenient functions, such as barcode and back calculation functions. |  Rechargeable battery pack: Rechargeable set. |
|  Data interface RS-232: To connect the balance to a printer, PC or network. |  Totalising level A: The weights of similar items can be added together and the total can be printed out. |  Mains adapter: 230V/50Hz in standard version for EU. On request GB, AUS or USA version available. |
|  RS-485 data interface: To connect the balance to a printer, PC or other peripherals. High tolerance against electromagnetic disturbance. |  Totalising level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display. Additional convenient functions, such as barcode and back calculation. |  Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request. |
|  USB data interface: To connect the balance to a printer, PC or other peripherals. |  Strain gauges: Electrical resistor on an elastic deforming body. | |
|  Bluetooth data interface: To transfer data from the balance to a printer, PC or other peripherals. |  Percentage determination: Determining the deviation in % from the target value (100 %). |  Single cell technology: Advanced version of the force compensation principle with the highest level of precision. |
|  WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals. |  Weighing units: Can be switched to e.g. non-metric units at the touch of a key. See balance model. Please refer to KERN's website for more details. |  Electromagnetic force compensation: Coil inside a permanent magnet. For the most accurate weighings. |
|  Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc. |  Weighing with tolerance range: Upper and lower limiting values can be programmed individually for e.g. dosing, sorting and portioning. |  Verification possible: The time required for verification is specified in the pictogram. |
|  Interface for second balance: For direct connection of a second balance. |  Vibration-free weighing: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value. |  DAkKS calibration possible: The time required for DAkKS calibration is shown in days in the pictogram. |
|  Network interface: For connecting the scale to an Ethernet network. With KERN products you can use a universal RS-232/LAN converter. |  Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram. For details see the glossary. |  Package shipment: The time required for internal shipping preparations is shown in days in the pictogram. |
|  GLP/ISO log: The balance displays the weight, date and time, regardless of a printer connection. |  ATEX explosion protection: Suitable for use in hazardous industrial environments, in which there is explosion danger. The ATEX marking is specified for each device. |  Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram. |
|  GLP/ISO log: With weight, date and time. Only with KERN printers, see "Accessories" |  Stainless steel: The balance is protected against corrosion. |  Warranty: The warranty period is shown in the pictogram. |
|  Piece counting: Reference quantities selectable. Display can be switched from piece to weight. | | |

Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2000 kg. In combination with a DAkKS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkKS calibration laboratory today is one of the most modern and best-equipped DAkKS calibration laboratories for balances, test weights and force-measurement in Europe.

Your KERN specialist dealer:

Thanks to the high level of automation, we can carry out DAkKS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkKS calibration of balances with a maximum load of up to 6 t
- DAkKS calibration of weights in the range of 1 mg - 500 kg
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkKS calibration certificates in the following languages D, GB, F, I, E, NL